



Spark H₂O: Trace Level Moisture Analyzer

At last, measurements made easy!

GASES & CHEMICALS

CEMS

ENERGY

ATMOSPHERIC

SEMI & HB LED

SYNGAS

LAB & LIFE SCIENCE

For the first time, powerful advanced spectroscopy is available at a popular price for a host of applications, from quality assurance to cylinder filling, as well as welding, medical, industrial and high-purity gas production; bulk delivery and distribution transfer points; and more. Say goodbye to cumbersome, complex, costly and labor-intensive 20th century technology. Gone is the need for calibration, spare parts, limited measurement ranges, and worries about drift and downtime. Plus, it's a joy to start up and to operate.

See Page 3 for
our optional
add-on packages!

The compact and affordable Spark H₂O offers:

- Powerful, proven Cavity Ring-Down Spectroscopy (CRDS) technology
- Self-tuning and auto-calibration
- Extremely low Cost of Ownership
- Ethernet, 4-20 mA and RS-232 connectivity
- Fast response with low gas consumption
- H₂O analysis over a vast range:
12 ppb to 2000 ppm (in N₂)!

The original maker of CRDS analyzers, Tiger Optics has been serving users worldwide for over a dozen years. We are in HyCO plants, with our Class I, Div 2 rated CO-rect analyzer; in nuclear plants, where we are Safety Integrity Level One (SIL 1) approved; and we are widely used in semiconductor fabs for bulk and specialty monitoring, in addition to toolmounted process control and QA/QC of purifiers and gas delivery systems. We are the designated standard under SEMI F-112-0613 for determining moisture dry-down characteristics of such systems. Tiger Optics was used by NIST to name the new hydrogen chloride protocol for continuous emissions monitoring, and we now measure HCl in stack gas at coal-fired utilities.

Put a little Spark in your life!

Tigeroptics

21ST

CENTURY SPECTROSCOPY

Spark H₂O

Trace Level Moisture Analyzer



Performance	
Operating range	See table below
Detection limit (LDL, 3σ/24h)	See table below
Precision (1σ, greater of)	± 0.75% or 1/3 of LDL
Accuracy (greater of)	± 4% or LDL
Speed of response	< 3 minutes to 90%
Environmental conditions	10°C to 40°C 30% to 80% RH (non-condensing)
Storage temperature	-10°C to 50°C

Gas Handling System and Conditions	
Wetted materials	316L stainless steel 10 Ra surface finish
Gas connections	1/4" male VCR inlet and outlet
Inlet pressure*	10 – 125 psig (1.7 – 9.6 bara)
Flow rate	~1.0 slpm (for N ₂)
Sample gases	Most inert, toxic, and passive matrices
Gas temperature	Up to 60°C

Dimensions	H x W x D [in (mm)]
Standard sensor	8.73 x 8.57 x 23.6 (222 x 218 x 599)
Sensor rack (fits up to two sensors)	8.73 x 19.0 x 23.6 (222 x 483 x 599)

Weight	
Standard sensor	32 lbs (14.5 kg)

Electrical	
Alarm indicators	2 user programmable 1 system fault Form C relays
Power requirements	90 – 240 VAC, 50/60 Hz
Power consumption	40 Watts max.
Signal output	Isolated 4–20 mA per sensor
User interfaces	5.7" LCD touchscreen 10/100 Base-T Ethernet 802.11g Wireless (optional) RS-232 Modbus TCP (optional)

Performance, H ₂ O:	Range	LDL (3σ)	Precision (1σ) @ zero
In Nitrogen	0 – 2000 ppm	12 ppb	4 ppb
In Oxygen	0 – 1000 ppm	6 ppb	2 ppb
In Argon	0 – 900 ppm	4.5 ppb	1.5 ppb
In Helium	0 – 450 ppm	3 ppb	1.0 ppb
In Hydrogen	0 – 1750 ppm	7.5 ppb	2.5 ppb
In Clean Dry Air (CDA)	0 – 1800 ppm	10 ppb	3 ppb
In Neon	0 – 450 ppm	30 ppb	10 ppb
In Krypton	0 – 1100 ppm	5.5 ppb	1.8 ppb
In Xenon	0 – 1300 ppm	7.5 ppb	2.5 ppb

* Inlet pressure as low as 0 psig available with Atmospheric Pressure Sampling option
Contact us for additional analytes and matrices • U.S. Patent # 7,277,177

Spark H₂O


Trace Level Moisture Analyzer

Optional Packages

Customize your Spark H₂O analyzer with these powerful add-ons:


Atmospheric Pressure Sampling

- Sample in Nitrogen and Clean Dry Air (CDA) with lower inlet pressure, down to 0 psig (may require vacuum pump)
- Wider inlet pressure range for H₂O measurement in Air Separation Units (ASUs)
- Expanded use with moisture standards and Low-Frost Point Generators (LFPGs)




Dew Point Measurement

- Moisture measurement can be displayed as Dew Point (in units of °C, °F or K) or Concentration (as volume or weight basis)
- Ideal for use as transfer standard for Dew Point-based moisture generators – no unit conversion necessary
- Wide Dew Point measurement range from -100°C to -13°C



Linear Fit Mode

- Linear $y = ax + b$ fit function permits user-defined calibration curves with programmable slope (a) and offset (b)
- Automatically adjusts readings to factor in dilution probes and sampling system offsets, while retaining the absolute data
- Enables calibration against external standards, when mandated by rules or regulations



Annual Remote Certification

- Low-cost and easy remote certification process, with no need to return the analyzer to the factory
- Annual re-certification by Tiger Optics ensures that your analyzer continues to meet its original specifications
- Up-to-date Verification Certificate to comply with your QA/QC standards



Tiger Optics, LLC

250 Titus Avenue, Warrington, PA 18976
Phone: +1 (215) 343 6600 • Fax: +1 (215) 343 4194
sales@tigeroptics.com • www.tigeroptics.com

